

AIROSOL COMPANY, INC.
MCKAY CHEMICALS **MECHANICS BRAND**
1101 Illinois, PO Box 120, Neodesha KS 66757 - Phone 620/325-2666

MATERIAL SAFETY DATA SHEET

EMERGENCY INFORMATION

MEDICAL: 1-800-633-9576

TRANSPORTATION: 1-800-535-5053

SECTION ONE

PRODUCT NAME: MECHANICS BRAND SILICONE SPRAY
PRODUCT CODE: 50607MB
ISSUE DATE: 10/29/2007, Revised 3/26/2009

SECTION TWO - HAZARDOUS COMPONENTS

| | EXPOSURE LIMITS | | | | CAS NO |
|---------------------------|-----------------|---------|-----------|-------|------------|
| | OSHA | ACGIH | OTHER | % | |
| Heptane | 400 ppm | 400 ppm | N/A | 25-30 | 142-82-5 |
| Isoparaffinic Hydrocarbon | ND | ND | 300 ppm** | 50-55 | 64742-47-8 |
| Isobutane | 800ppm | 800ppm | N/A | 10-15 | 75-28-5 |
| Propane | 1000ppm | 1000ppm | N/A | 10-15 | 74-98-6 |

ABBREVIATIONS: *Stel (ACGIH-TLV) N/A: Not Applicable, ND: Not Determined, NE: None Established

SECTION THREE - PHYSICAL DATA

BOILING POINT: ND
VAPOR DENSITY (AIR=1) Heavier than
SOLUBILITY IN WATER % BY WT. Insoluble
EVAPORATION RATE (BUTYL ACETATE=1): Faster Than

VAPOR PRESSURE (mmHg or psig @ 70°F): 40 psig
SPECIFIC GRAVITY (H₂O=1): 0.74-0.76
VOC CONTENT % BY WT: 60%
APPEARANCE AND ODOR: Clear , Solvent odor

SECTION FOUR - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: ND FLAMMABLE LIMITS: UEL 11.6% LEL 0.6%

EXTINGUISHING MEDIUM: Dry chemical, foam or carbon dioxide.

FIRE AND EXPLOSION HAZARD DATA:

SPECIAL FIRE FIGHTING PROCEDURES: Treat as a petroleum fire. Do not use solid stream of water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA in positive pressure mode with full face shield. The flammable components are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition as vapor may ignite. Carbon oxides may be formed.

SECTION FIVE - REACTIVITY DATA

STABILITY: This product is stable, avoid open flames and high temperatures (above 120°F) and direct sunlight.

INCOMPATIBILITY: This product could react vigorously with oxidizing materials. A very dangerous fire and explosion hazard when exposed to heat or flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Silicone dioxide, carbon dioxide, and traces of incompletely burned carbon products, fumes, smoke, carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

PRODUCT NAME: MECHANICS BRAND SILICONE SPRAY
PRODUCT CODE: 50607MB

SECTION SIX - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Product can be considered irritating, causing redness, itching and burning sensation. No evidence has been found to support damaging eye tissue, unless product is sprayed directly into eye at close range.
SKIN CONTACT: Low order of toxicity, frequent or prolonged contact may irritate and cause dermatitis.
SKIN ABSORPTION: No evidence if skin absorption occurring.
INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. Considered low order of toxicity.
INHALATION: High vapor aerosol concentrations (greater then approximately 100ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous systems effects, including death. Could be considered a narcotic in high concentrations.
HUMAN SYSTEMIC EFFECTS: Hallucinations, structural change in nerve or sheath. Hexane is a teratogenic and causes reproductive effects. Mutation data has been reported.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. Make sure each eyelid is lifted to allow complete rinsing of solution. Consult physician promptly.
SKIN CONTACT: Remove contaminated clothing and completely wash exposed areas with soap and water. Wash clothing before wearing.
INHALATION: Remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. Call physician immediately if symptoms persist.
INGESTION: Unlikely, as an aerosol, but if ingested do not induce vomiting. Give 2 full glasses of water. Keep victim's head below hips or on their left side with their head down. Call physician or poison control center immediately.

SECTION SEVEN - ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO TAKE FOR SPILLS/LEAKS: Eliminate all sources of ignition, ventilate enclosed areas. Soap up with absorbent. Place in non-leaking containers for disposal.
WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

SECTION EIGHT - HANDLING AND STORAGE PRECAUTIONS

Store in tightly sealed containers. Keep away from heat, sparks and open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Do not throw empty containers into fires. Read label completely before using.

SECTION NINE - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): Concentration in air determines protection needed. Use only NIOSH certified respiratory protection. Respiratory protection usually not needed unless product is heated or misted. Half mask air purifier, respirator with dust/mist filter or HEPA filter cartridge is acceptable to 10 times the exposure limit.
VENTILATION: Local mechanical exhaust ventilation capable of maintaining emissions at the point of use below the PEL/TLV.
PROTECTIVE GLOVES: Any lined non-permeable rubber gloves.
EYE PROTECTION: Chemical resistant safety glasses with protective side shields.
OTHER PROTECTIVE EQUIPMENT: Non-permeable clothing to protect all skin from liquid contact. Do not eat or drink around this product when using it. Wash exposed areas with soap and water when finished using.

SECTION TEN - REGULATORY INFORMATION

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

PRODUCT NAME: MECHANICS BRAND SILICONE SPRAY
PRODUCT CODE: 50607MB

SECTION TEN - REGULATORY INFORMATION (continued)

CHEMICAL CAS NUMBER CONCENTRATION %
FEDERAL EPA: Comprehensive Environmental Response, Compensation, And Liability Act of 1980 (Cercla) requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (Rqs) In 40 CFR 302.4.

CHEMICAL CAS NUMBER CONCENTRATION % UPPER BOUND RQs IN #S
CALIFORNIA PROPOSITION 65: None listed
MASSACHUSETTS RIGHT TO KNOW: Yes

| | | |
|-----------|----------|-------|
| Heptane | 142-82-5 | 25-30 |
| Isobutane | 75-28-5 | 10-15 |
| Propane | 74-98-6 | 10-15 |

PENNSYLVANIA RIGHT TO KNOW: Yes
Heptane 142-82-5 25-30
Isobutane 75-28-5 10-15
Propane 74-98-6 10-15

NEW JERSEY RIGHT TO KNOW: Yes
Heptane 142-82-5 25-30
Isobutane 75-28-5 10-15
Propane 74-98-6 10-15

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS: Listed

CALIFORNIA VOC'S: 60%

NFPA RATING AS AN AEROSOL: Level 3

HMS: HEALTH 2 REACTIVITY 0 FLAMMABILITY 4

SARA HAZARD CATEGORIES AND LISTS

PRODUCT HAZARD CATEGORIES

CHRONIC HEALTH: Yes

ACUTE HEALTH: Yes

FIRE HAZARD: Yes

PRESSURE HAZARD: Yes

| CARCINOGENITY | CHEMICAL | IARC | NTP | OSHA |
|---------------|----------|------|-----|------|
| NOT LISTED | | | | |

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.

