

AIROSOL COMPANY, INC.

1206 Illinois

Phone 620-325-2666

Neodesha KS 66757

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

PRODUCT NAME: Mechanics Brand Trans Tune

PRODUCT NUMBER: 50106MB

Medical Emergency: 1-800-633-9576 (8AM-5PM central time)

CAS NUMBER: Mixture See Section 3.

INFOTRAC: 1-800-535-5053

PRODUCT FAMILY:

HMIS: Health 2 Reactivity 0 Flammability 1

SECTION 2: HAZARD IDENTIFICATION

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

ASPIRATION HAZARD - Category 1



Danger

May be fatal if swallowed and enters airways.

This product contains an additive that alone causes eye and skin irritation, but as a mixture does not carry the classification of corrosive. Caution should still be made to prevent material from touching eyes or skin.

Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Defatting to the skin.

Read entire label before use.

OSHA Health Hazard Classification

Irritant YES Toxic NO
Sensitizer NO Highly toxic NO
Corrosive NO Carcinogenic NO

OSHA Physical Hazard Classification

Combustible NO Explosive NO Pyrophoric NO
Flammable NO Oxidizer NO Water-Reactive NO
Compressed Gas NO Organic Peroxide NO Unstable NO

SECTION 3: COMPOSITION

COMPONENT NAME(S)

CAS NO

CONCENTRATION (%)

Distillates (petroleum), hydrotreated heavy naphthenic	75-80	64742-52-5
Methacrylate copolymer	5-10	Mixture

PRODUCT NAME: Mechanics Brand Trans Tune
PRODUCT NUMBER: 50106MB

SECTION 4: FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If spontaneous vomiting is about to occur, place victims head between their knees to prevent aspiration. Call a physician or transport to an emergency facility immediately.

IF IN EYES: Rinse cautiously with water for several minutes. Lift upper and lower eyelids to ensure proper rinsing. Get medical attention if irritation persists.

IF ON SKIN: Wash skin with soap and water. Remove contaminated clothing and launder it before reuse. Should any irritation persist, get medical attention.

IF INHALED: Increase fresh air circulation or leave area. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

NFPA Flammability Classification: LEVEL Aerosol

FLASH POINT: Not Determined **FLAMMABLE LIMITS: UEL** Not available **LEL** Not available

EXTINGUISHING MEDIUM: AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Keep exposed containers cool with water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse any flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.

Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

SECTION 7: HANDLING AND STORAGE

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

PRODUCT NAME: Mechanics Brand Trans Tune
PRODUCT NUMBER: 50106MB

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Control airborne concentrations below the exposure limits see below. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPMENT: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. Minimum requirements are: SAFETY GLASSES and GLOVES.

RESPIRATORY PROTECTION (SPECIFY TYPE): If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION: For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier)

BODY PROTECTION: To prevent repeated or prolonged skin contact, use protective clothing impervious to this product. Selection of specific items such as gloves, boots, apron, or full body suit will depend on operation.

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 4/2014). TWA: 5 mg/m ³ 8 hours. Form: inhalable fraction NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid	COLOR: Amber	ODOR: petroleum oil
SPECIFIC GRAVITY: 0.80-0.85 (Water =1)	pH: N/A	VAPOR DENSITY (Air =1): N/A
BOILING POINT RANGE: N/D	MELTING POINT /FREEZING POINT: N/D	
VAPOR PRESSURE (mmHg or psig @70°F):	N/A	VISCOSITY (cps @ 70°F) N/D
SOLUBILITY IN WATER % BY WT. Nil		
VOLATILE ORGANIC COMPOUNDS (VOCs) Content: Not regulated %		

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable, avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition and direct sunlight.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents, acids, halogens and halogenated compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur

PRODUCT NAME: Mechanics Brand Trans Tune
PRODUCT NUMBER: 50106MB

SECTION 11: TOXICOLOGICAL INFORMATION

No toxicological studies have been conducted on this product.

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated heavy naphthenic	ASPIRATION HAZARD - Category 1

ATEmix > 10.00 mg/kg

Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying or cracking of the skin.

SECTION 12: ECOLOGICAL INFORMATION

No ecological studies have been conducted on this product.

ECOTOXICITY: If spilled this any water or soil contaminated may be hazardous to human, animal and aquatic life.

ENVIRONMENTAL FATE: The chemicals in this product are potentially toxic to freshwater and salt water ecosystems. They will normally float on water with their lighter components evaporating rapidly. In stagnant or slow-flowing waterways, a hydrocarbon layer can cover a large surface area. As a result this layer might limit or eliminate natural atmospheric oxygen transport into the water. Which with time could lead to a fish kill or an anaerobic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use. It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

SECTION 14: TRANSPORT INFORMATION

DOT STATUS: This material is regulated by the U.S. Department of Transportation (DOT).

PROPER SHIPPING NAME: (to ship on the ocean):

PETROLEUM, OIL, GREASE, & RELATED PRODUCTS NON-HAZARDOUS, NOT REGULATED

HAZARD CLASS: N/A

PACKING GROUPS: N/A

PLACARDS: None Required

EMERGENCY RESPONSE GUIDE NO: N/A

PRODUCT NAME: Mechanics Brand Trans Tune
PRODUCT NUMBER: 50106MB

SECTION 15: REGULATORY INFORMATION

311/312 HAZARD CATEGORIES:

Fire Hazard: NO Pressure Hazard: NO Reactivity Hazard: NO Immediate Hazard: NO Delayed Hazard: NO

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
----------	------------	-----------------

None listed

FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA)

requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
----------	------------	-----------------------------	----------

None listed

CALIFORNIA PROPOSITION 65 None listed

MASSACHUSETTS RIGHT TO KNOW: No

PENNSYLVANIA RIGHT TO KNOW: No

NEW JERSEY RIGHT TO KNOW: No

SECTION 16: OTHER INFORMATION

REVISION INFORMATION

VERSION NUMBER:1.0001

REVISION DATE: 11/4/2005, 3/26/2009, 5/28/2015, 11/17/2015

PRINT DATE:

ABBREVIATIONS:

N/A: Not Applicable

N/D: Not Determined

NE: Not Established

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health

Administration

HMIS: Hazardous Materials Information System

NFPA: National Fire Protection Association

EPA: US Environmental Protection

Agency NIOSH: National institute of Occupational Safety and Health

DISCLAIMER OF LIABILITY:

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.