

SAFETY DATA SHEET

Issuing Date 10-Nov-2015

Revision Date 10-Nov-2015

Revision Number 4



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name 50213MB Mechanics Brand Carb Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use Fuel Injector/Carburetor Cleaner

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Airosol Company, Inc.

Supplier Address P.O. Box 120
1206 Illinois St.
Neodesha
KS
66757
US

Emergency telephone number

24 hour INFOTRAC 1-800-535-5053 (North America)
1-352-323-3500 (International)

Company Phone Number 1-800-633-9576

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).


Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4



Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger		
Hazard Statements	Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes skin irritation Causes serious eye irritation Suspected of damaging fertility or the unborn child Causes damage to organs May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated		
			
Appearance	Clear, colorless	Physical state	Liquid spray Aerosol
			Odor Solvent

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Pressurized container: Do not pierce or burn, even after use
- Do not spray on an open flame or other ignition source

Precautionary Statements - Response

- Specific treatment (see .? on this label)
- Specific treatment (see supplemental first aid instructions on this label)
- IF exposed: Call a POISON CENTER or doctor/physician



Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
Call a POISON CENTER or doctor/physician if you feel unwell
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

Rinse mouth
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Store in a well-ventilated place
Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

7.3005 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects
Harmful to aquatic life
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	
Acetone	67-64-1	30 - 60	
Toluene	108-88-3	10 - 30	
Methyl alcohol	67-56-1	10 - 30	
Carbon Dioxide	124-38-9	5 - 10	

4. FIRST AID MEASURES

First aid measures

<u>General Advice</u>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.
--	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Uniform Fire Code	Aerosols: Level III Irritant: Liquid
--------------------------	---

Explosion Data

Sensitivity to Mechanical Impact	Yes.
---	------

Sensitivity to Static Discharge	Yes.
--	------

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Stop leak if you can do it without risk.
-----------------------------	--

Other Information	Ventilate the area.
--------------------------	---------------------

Environmental precautions

Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.
----------------------------------	--

Methods and material for containment and cleaning up

Methods for containment	If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.
--------------------------------	--

Methods for cleaning up	Do not direct water at spill or source of leak.
--------------------------------	---

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Use only with adequate ventilation and in closed systems. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Carbon Dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid spray, Aerosol	Odor	Solvent
Appearance	Clear, colorless	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.7967	None known	
Water Solubility	Insoluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available



Particle Size No data available
Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain. May cause irritation.
Skin contact	Specific test data for the substance or mixture is not available. Harmful in contact with skin. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways. Harmful if swallowed. (based on components). Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Methyl alcohol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

Information on toxicological effects



Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		

*IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity Contains a known or suspected reproductive toxin.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity Possible risk of irreversible effects. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure. Prolonged exposure may cause chronic effects. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects.

Target Organ Effects Respiratory system. Eyes. Skin. Reproductive System. Central Nervous System (CNS). Liver. Kidney.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

490.00 mg/kg

ATEmix (dermal)

1,561.00 mg/kg

ATEmix (inhalation-dust/mist)

2.50 mg/l

ATEmix (inhalation-vapor)

16.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone 67-64-1		96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L
Toluene 108-88-3	96h EC50: > 433 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 12.5 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 15.22 - 19.05 mg/L (Pimephales promelas) 96h LC50: 5.89 - 7.81 mg/L (Oncorhynchus mykiss) 96h LC50: 14.1 - 17.16 mg/L (Oncorhynchus mykiss) 96h LC50: = 5.8 mg/L (Oncorhynchus mykiss) 96h LC50: = 12.6 mg/L (Pimephales promelas) 96h LC50: 11.0 - 15.0 mg/L (Lepomis macrochirus) 96h LC50: = 54 mg/L (Oryzias latipes) 96h LC50: = 28.2 mg/L (Poecilia reticulata) 96h LC50: 50.87 - 70.34 mg/L (Poecilia reticulata)	EC50 = 19.7 mg/L 30 min	48h EC50: 5.46 - 9.83 mg/L 48h EC50: = 11.5 mg/L
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.65
Methyl alcohol 67-56-1	-0.77

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Should not be released into the environment. Dispose of contents/containers in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number U220 U154 U002

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable
Methyl alcohol 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D

TDG

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

MEX

UN-No. UN1950



Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

ICAO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

IATA

UN-No. UN1950
Proper Shipping Name AEROSOLS, FLAMMABLE
Hazard Class 2.1
ERG Code 10L
Description UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG/IMO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
EmS-No. F-D, S-U
Description UN1950, AEROSOLS, 2.1

RID

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Description UN1950, AEROSOLS, 2.1

ADR

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Tunnel restriction code D
Description UN1950, AEROSOLS, 2.1

ADN

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Special Provisions 190, 327, 344, 625
Description UN1950, AEROSOLS, 2.1
Hazard Labels 2.1
Limited Quantity 1 L
Ventilation VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	10 - 30	1.0
Methyl alcohol - 67-56-1	67-56-1	10 - 30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental
Methyl alcohol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone 67-64-1	X	X	X	X	
Toluene 108-88-3	X	X	X	X	X
Methyl alcohol 67-56-1	X	X	X	X	X
Carbon Dioxide 124-38-9	X	X	X		-
Supplier Trade Secret			X	X	X



International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Acetone 67-64-1 (30 - 60)		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³
Toluene 108-88-3 (10 - 30)		Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³
Methyl alcohol 67-56-1 (10 - 30)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³
Carbon Dioxide 124-38-9 (5 - 10)	-	Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m ³ Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 4	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 3 *	Flammability 4	Physical Hazard 0	

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 10-Nov-2015
Revision Date 10-Nov-2015
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

