

# AIROSOL COMPANY, INC.

1206 Illinois

Phone 620-325-2666

Neodesha KS 66757

## SAFETY DATA SHEET

### SECTION 1: IDENTIFICATION

PRODUCT NAME: **Mechanics Brand Undercoating Spray**

PRODUCT NUMBER: **50924MB**

Medical Emergency: 1-800-633-9576 (8AM-5PM central time)

INFOTRAC: 1-800-535-5053

CAS NUMBER: Mixture See Section 3.

PRODUCT FAMILY: **Multi-Purpose Lubricant**

**NFPA RATING AS AN AEROSOL:** Level Three

### SECTION 2: HAZARD IDENTIFICATION

#### EMERGENCY OVERVIEW:

**DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED.**



**Major Route(s) of Entry:** ASPIRATION HAZARD. LUNGS.

Extremely Flammable Aerosols	Category 1
Acute Oral Toxicity	Category 4
Acute Toxicity-Inhalation	Category 4
Skin Irritation	Category 2
Eye Irritation	Category 2
Target organ toxicity, repeat exposure	Category 2

#### Signal Word

**DANGER**

#### Hazard Statements

Harmful if swallowed.

Harmful if inhaled.

Causes skin irritation.

Causes eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Extremely flammable aerosol. Pressurized container: Do not pierce or burn, even after use.

#### Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Use in a well-ventilated area.

Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source.

#### Precautionary Statements - Storage

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

PRODUCT NAME: **Mechanics Brand Undercoating Spray**  
PRODUCT NUMBER: 50924MB

### SECTION 3: COMPOSITION

HAZARDOUS COMPONENTS	%	CAS NO
Mineral Spirits	10-20	8052-41-3
Petroleum Asphalt	20-45	8052-42-4
Propane	10-15	74-98-6
Butane	1-5	106-97-8

Abbreviations

NE: None established N/A: Not applicable \*: ACGIH "STEL" Guidelines ND: Not Determined STEL: Short Term Exposure Limits

### SECTION 4: FIRST AID MEASURES

**Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.**

#### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention. Have container label at if seeking medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing if eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do not induce vomiting  
Rinse mouth.

### SECTION 5: FIRE FIGHTING MEASURES

**NFPA Flammability Classification: LEVEL 3 Aerosol**

**FLASH POINT:** Not Determined **FLAMMABLE LIMITS: UEL 9.5 % LEL 0.9 %**

### SECTION 5: FIRE FIGHTING MEASURES (continued)

**EXTINGUISHING MEDIUM:** AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

**SPECIAL FIREFIGHTING PROCEDURES:** Do not use jet stream of water. Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Do not use water jet. Keep exposed containers cool with water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse any flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

PRODUCT NAME: **Mechanics Brand Undercoating Spray**  
PRODUCT NUMBER: 50924MB

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.** Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

## SECTION 7: HANDLING AND STORAGE

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Control airborne concentrations below the exposure limits see below. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

**PERSONAL PROTECTIVE EQUIPEMNT:** Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. Minimum requirements are: SAFETY GLASSES and GLOVES.

**RESPIRATORY PROTECTION (SPECIFY TYPE):** If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

**HAND PROTECTION:** For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

**EYE PROTECTION:** Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier)

**BODY PROTECTION:** To prevent repeated or prolonged skin contact, use protective clothing impervious to this product. Selection of specific items such as gloves, boots, apron, or full body suit will depend on operation.

OCCUPATIONAL EXPOSURE GUIDELINES:

### HAZARDOUS COMPONENTS

	OSHA PEL	ACGIH
Petroleum Distillates	500 ppm	100 ppm
Propane	1000 ppm	NE
Butane	800 ppm	800 ppm

Abbreviations

NE: None established N/A: Not applicable \*: ACGIH "STEL" Guidelines ND: Not Determined STEL: Short Term Exposure Limits

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Aerosol	COLOR: Black	ODOR: Petroleum
SPECIFIC GRAVITY: 1.0-1.4 (Water =1) pH: N/A		VAPOR DENSITY (Air =1): Heavier Than
VAPOR PRESSURE (mmHg or psig @70°F): 50-70 psig		VISCOSITY (cps @ 70°F) N/D
SOLUBILITY IN WATER % BY WT.: Insoluble		MELTING POINT /FREEZING POINT: N/D
VOLATILE ORGANIC COMPOUNDS (VOCs) Content: 26 %		BOILING POINT RANGE: N/D

PRODUCT NAME: **Mechanics Brand Undercoating Spray**  
PRODUCT NUMBER: 50924MB

## SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** Stable, avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition and direct sunlight.

**INCOMPATIBILITY:** Strong oxidizers and halogens.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide, carbon monoxide, nitrogen, and sulfur.

**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

##### **Eye Contact**

Mild eye irritation.

##### **Skin Contact**

Causes skin irritation. Harmful if prolonged contact with skin occurs.

##### **Inhalation**

Harmful if inhaled.

##### **Ingestion**

Harmful if swallowed.

### Component Information

<b>Chemical Name</b>	<b>Oral LD50</b>	<b>Dermal</b>	<b>Inhalation</b>
Petroleum distillates	> 5,000 mg/kg rat	No Information	No information
Propane	No information	No information	658 mg/l/4h rat
Butane	No information	No information	30957 mg/m <sup>3</sup> 4h rat

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Carcinogenicity**

Not classifiable as a human carcinogen

#### **Reproductive toxicity**

No information.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

## SECTION 12: ECOLOGICAL INFORMATION

No ecological studies have been conducted on this product.

Petroleum distillates, hydrotreated light Chronic NOEL 0.48 mg/l Daphnia 21 days.

**ECOTOXICITY:** If spilled this any water or soil contaminated may be hazardous to human, animal and aquatic life.

**ENVIRONMENTAL FATE:** The chemicals in this product are potentially toxic to freshwater and salt water ecosystems. They will normally float on water with their lighter components evaporating rapidly. In stagnant or slow-flowing waterways, a hydrocarbon layer can cover a large surface area. As a result this layer might limit or eliminate natural atmospheric oxygen transport into the water. Which with time could lead to a fish kill or an anaerobic environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use. It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

PRODUCT NAME: **Mechanics Brand Undercoating Spray**  
PRODUCT NUMBER: 50924MB

## SECTION 14: TRANSPORT INFORMATION

DOT STATUS: This material is regulated by the U.S. Department of Transportation (DOT).

PROPER SHIPPING NAME: (to ship on the ocean):

**UN1950, AEROSOLS, FLAMMABLE (each not exceeding 1L capacity), 2.1, LTD. QTY**

HAZARD CLASS: 2.1

PACKING GROUPS: None for aerosols

PLACARDS: None Required

EMERGENCY RESPONSE GUIDE NO: 126

## SECTION 15: REGULATORY INFORMATION

### 311/312 HAZARD CATEGORIES:

Fire Hazard: YES Pressure Hazard: YES Reactivity Hazard: NO Immediate Hazard: YES Delayed Hazard: NO

### SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
----------	------------	-----------------

None Listed.

### FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA)

requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
----------	------------	-----------------------------	----------

None Listed.

CALIFORNIA PROPOSITION 65 None listed

## SECTION 15: REGULATORY INFORMATION (continued)

MASSACHUSETTS RIGHT TO KNOW: Yes

PENNSYLVANIA RIGHT TO KNOW: Yes

NEW JERSEY RIGHT TO KNOW: Yes

Stoddard Solvent (Mineral Spirits)	8052-41-3	10-20
Propane	74-98-6	10-15
Butane	106-97-8	1-5

CALIFORNIA VOC'S: 26 %

NFPA RATING AS AN AEROSOL: Level Three

## SECTION 16: OTHER INFORMATION

### REVISION INFORMATION

VERSION NUMBER: 1.0004

REVISION DATE: 3/19/2008, 3/29/2009, 4/4/2011, 6/4/2015

PRINT DATE:

### ABBREVIATIONS:

N/A: Not Applicable

N/D: Not Determined

NE: Not Established

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

HMIS: Hazardous Materials Information System

NFPA: National Fire Protection Association

EPA: US Environmental Protection Agency NIOSH: National Institute of Occupational Safety

and Health

### DISCLAIMER OF LIABILITY:

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.

