

SAFETY DATA SHEET**SECTION 1: IDENTIFICATION****PRODUCT NAME: McKay Fuel Injector Cleaner****PRODUCT NUMBER: 50122**

CAS NUMBER: Mixture See Section 3.

PRODUCT FAMILY: Automotive Aftermarket

Medical Emergency: 1-800-633-9576 (8AM-5PM central time)

INFOTRAC: 1-800-535-5053

SECTION 2: HAZARD IDENTIFICATION**EMERGENCY OVERVIEW:**

FLAMMABLE LIQUIDS - Category 3

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation and Narcotic effects] - Category 3

ASPIRATION HAZARD - Category 1

AQUATIC TOXICITY (ACUTE) -

Category 1 AQUATIC TOXICITY

(CHRONIC) - Category 1



Flammable liquid and vapor. Causes serious eye damage.

May be fatal if swallowed and enters airways. May cause respiratory irritation.

May cause drowsiness and dizziness.

Very toxic to aquatic life with long lasting effects

Wear protective gloves and eye/face protection. Do not breathe vapor.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Use explosion-proof electrical/ventilating/lighting/material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid release to the environment.

Collect spillage.

IF SWALLOWED: Get immediate medical attention. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Get immediate medical attention.

IF IN EYES: Get immediate medical attention. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash hands after handling.

Store locked up. Use in a well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 3: COMPOSITION

Chemical Name	CAS #	%by weight
Petroleum Distillates, Hydrotreated light	64742-47-8	90-95
Solvent naphtha (petroleum), light aromatic	64742-95-6	1-3
Alkylphenol polyoxyalkylamine	Mixture	1-3
Benzene, 1,2,4-trimethyl-	95-63-6	0.5 - 1
Benzene, 1,3,5-trimethyl-	108-67-8	0.25-0.50
N-Propylbenzene	103-65-1	0.25-0.50
Xylene	1330-20-7	<0.25
Cumene	98-82-8	<0.25
Benzene, 1,2,3-trimethyl-	526-73-8	<0.25

SECTION 4: FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If spontaneous vomiting is about to occur, place victims head between their knees to prevent aspiration. Call a physician or transport to an emergency facility immediately.

IF IN EYES: Rinse cautiously with water for several minutes. Lift upper and lower eyelids to ensure proper rinsing. Get medical attention if irritation persists.

IF ON SKIN: Wash skin with soap and water. Remove contaminated clothing and launder it before reuse. Should any irritation persist, get medical attention.

IF INHALED: Increase fresh air circulation or leave area. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABLE LIQUIDS- Category 3

FLASH POINT: Not Determined **FLAMMABLE LIMITS: UEL 5.5 % LEL 0.6 %**

EXTINGUISHING MEDIUM: AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 5: FIRE FIGHTING MEASURES (continued)

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Keep exposed containers cool with water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse any flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.

Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

SECTION 7: HANDLING AND STORAGE

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Control airborne concentrations below the exposure limits see below. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPMENT: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. Minimum requirements are: SAFETY GLASSES and GLOVES.

RESPIRATORY PROTECTION (SPECIFY TYPE): If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION: For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier)

BODY PROTECTION: To prevent repeated or prolonged skin contact, use protective clothing impervious to this product. Selection of specific items such as gloves, boots, apron, or full body suit will depend on operation.

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

OCCUPATIONAL EXPOSURE GUIDELINES:

Substance	Applicable Workplace Exposure Levels	
	OSHA PEL	ACGIH
Petroleum Distillates, hydrotreated light		ACGIH TLV (United States, 4/2014 Absorbed through skin. TWA: 200 mg/m3(as total hydrocarbon vapor) 8 hours
Benzene, 1,2,4-trimethyl-		ACGIH (United States, 1999). TWA: 25 ppm
trimethylbenzenes		ACGIH (United States, 1999). TWA: 25 ppm
Xylene		ACGIH (United States, 1996). TWA: 100 ppm
Cumene		STEL: 150 ppm OSHA (United States). TWA: 100 ppm ACGIH (United States, 1994). Absorbed through skin. TWA: 50 ppm
		OSHA (United States, 1989). Absorbed through skin. TWA: 50 ppm
Benzene, 1,2,3-trimethyl-		ACGIH (United States, 1999). TWA: 25 ppm

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid	COLOR: Light Yellow	ODOR: Mild Hydrocarbon
SPECIFIC GRAVITY: 0.75-0.85 (Water =1)	pH: N/A	VAPOR DENSITY (Air =1):
BOILING POINT RANGE: N/D	MELTING POINT /FREEZING POINT: N/D	
VAPOR PRESSURE (mmHg or psig @70°F):	psig	VISCOSITY (cps @ 70°F) N/D
SOLUBILITY IN WATER % BY WT.: Nil		
VOLATILE ORGANIC COMPOUNDS (VOCs) Content: 100 %		

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable, avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition and direct sunlight.

INCOMPATIBILITY: Avoid contact with s

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, and carbon monoxide, irritating aldehydes and ketones may form upon burning.

HAZARDOUS POLYMERIZATION: Will not occur

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 11: TOXICOLOGICAL INFORMATION

No toxicological studies have been conducted on this product.

Product/ingredient name	Result	Species	Dose	Exposure
Petroleum Distillates, hydrotreated light	LD50 Dermal	Rabbit	>2000 mg/kg	--
	LD 50 Oral	Rat	> 5000 mg/kg	--
Solvent naphtha (petroleum), light aromatic	LOS0 Oral	Rat	8400 mg/kg	
	LOS0 Oral	Rat Rat		
	LOS0 Oral	Rabbit Rat	5000 mg/kg	
	LOS0 Dermal	Rat	2900 mg/kg	
	LOS0 Oral		mg/kg	
	LOS0 Oral		3160 mg/kg	
Benzene, 1,2,4-trimethyl-	LC50 Inhalation Vapor	Rat	18000 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat Rat	24000 mg/m ³	4 hours
	LOS0 Oral		mg/m ³	
Benzene, 1,3,5-trimethyl-	LOS0 Dermal	Rabbit Rat	>14100 mg/kg	
	LOS0 Oral	Rat - Male Rat	4300 mg/kg	
N-Propylbenzene	LC50 Inhalation Vapor	Rabbit	mg/kg	4 hours
	LOS0 Dermal	Mouse Rat	3523 mg/kg	
Xylene	LOS0 Dermal	Rat	mg/kg	
	LOS0 Oral		5000 to 8500 mg/kg	
	LOS0 Oral		8500 mg/kg	
	LC50 Inhalation Vapor		ppm	4 hours
Cumene	LC50 Inhalation Vapor		10578 mg/kg	

ASPIRATION HAZARD – Category 1

Specific target organ toxicity (single exposure) Category 3 Narcotic effects. Routes of entry anticipated: Oral, dermal, inhalation.

Contains at less than 5 % materials that may cause damage to the following organs: blood, kidneys, liver, gastrointestinal tract, upper respiratory tract, eyes, central nervous system (CNS). Irritating to the respiratory system. Ingestion may cause gastrointestinal irritation and diarrhea. May cause skin sensitization. Repeated exposure may cause skin dryness and cracking. Irritating to the eyes.

SECTION 12: ECOLOGICAL INFORMATION

No ecological studies have been conducted on this product.

ECOTOXICITY: If spilled this any water or soil contaminated may be hazardous to human, animal and aquatic life.

ENVIRONMENTAL FATE: The chemicals in this product are potentially toxic to freshwater and salt water ecosystems. They will normally float on water with their lighter components evaporating rapidly. In stagnant or slow-flowing waterways, a hydrocarbon layer can cover a large surface area. As a result this layer might limit or eliminate natural atmospheric oxygen transport into the water. Which with time could lead to a fish kill or an anaerobic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use. It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 14: TRANSPORT INFORMATION

DOT STATUS: This material is regulated by the U.S. Department of Transportation (DOT).

PROPER SHIPPING NAME: (to ship on the ocean):
UN1993,FLAMMABLE LIQUIDS, N.O.S.,(petroleum distillates),3,PGII, LTD.QTY.

HAZARD CLASS: 3 PACKING GROUPS: II PLACARDS: Flammable Liquid 3

SECTION 15: REGULATORY INFORMATION

311/312 HAZARD CATEGORIES:

Fire Hazard: YES Pressure Hazard: NO Reactivity Hazard: NO Immediate Hazard: NO Delayed Hazard: NO

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
Benzene. 1.2.4-trimethyl-	95-63-6	0.5 - 1
Benzene. 1.3.5-trimethyl-	108-67-8	0.25-0.50
N-Propylbenzene	103-65-1	0.25-0.50
Xylene	1330-20-7	<0.25
Cumene	98-82-8	<0.25
Benzene, 1,2,3-trimethyl-	526-73-8	<0.25

FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA)

requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
Xylene	1330-20-7	<0.25	100
Cumene	98-82-8	<0.25	5,000

CALIFORNIA PROPOSITION 65: Yes

Benzene. 1.2.4-trimethyl-	95-63-6	0.5 - 1
Benzene. 1.3.5-trimethyl-	108-67-8	0.25-0.50
N-Propylbenzene	103-65-1	0.25-0.50
Xylene	1330-20-7	<0.25
Cumene	98-82-8	<0.25
Benzene. 1.2.3-trimethyl-	526-73-8	<0.25

MASSACHUSETTS RIGHT TO KNOW: Yes

PENNSYLVANIA RIGHT TO KNOW: Yes

NEW JERSEY RIGHT TO KNOW: Yes

Benzene. 1.2.4-trimethyl-	95-63-6	0.5 - 1
Benzene. 1.3.5-trimethyl-	108-67-8	0.25-0.50
N-Propylbenzene	103-65-1	0.25-0.50
Xylene	1330-20-7	<0.25
Cumene	98-82-8	<0.25
Benzene. 1.2.3-trimethyl-	526-73-8	<0.25

PRODUCT NAME: McKay Fuel Injector Cleaner
PRODUCT NUMBER: 50122

SECTION 16: OTHER INFORMATION

REVISION INFORMATION

VERSION NUMBER: 1.0003

REVISION DATE: 11/4/2005, 3/26/2009, 6/18/2015

PRINT DATE:

ABBREVIATIONS:

N/A: Not Applicable

N/D: Not Determined

NE: Not Established

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

HMS: Hazardous Materials Information System

NFPA: National Fire Protection Association

EPA: US Environmental Protection Agency NIOSH: National institute of Occupational Safety

and Health

DISCLAIMER OF LIABILITY:

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.