

AIROSOL COMPANY, INC.

1206 Illinois

Phone 620-325-2666

Neodesha KS 66757

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

PRODUCT NAME: **McKay Belt Grip**

PRODUCT NUMBER: 50603

CAS NUMBER: Mixture See Section 3.

PRODUCT FAMILY: **Automotive After Market**

Medical Emergency: 1-800-633-9576 (8AM-5PM central time)

INFOTRAC: 1-800-535-5053

NFPA RATING AS AN AEROSOL: Level Three

SECTION 2: HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED.



Major Route(s) of Entry: ASPIRATION HAZARD. EYES. LUNGS. SKIN.

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Eye Irritation	Category 2A

Signal Word Danger

Hazard Statements

Causes Eye irritation.

Causes skin irritation.

May be fatal if swallowed and enters airways.

May cause drowsiness and dizziness.

Extremely flammable aerosol.

Repeated exposure may cause skin dryness or cracking.

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

PRODUCT NAME: **McKay Belt Grip**
PRODUCT NUMBER: 50603

SECTION 2: HAZARD IDENTIFICATION (CONTINUED)

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

SECTION 3: COMPOSITION

HAZARDOUS COMPONENTS	%	CAS NO
Heptane	35-40	64742-49-0
Acetone	5-10	67-64-1
Dimerized Rosin	5-10	65997-05-9
Resin and rosin acids, methyl ester	10-15	68186-14-1
Propane	10-15	74-98-6
Butane	10-15	106-97-8

Abbreviations

NE: None established N/A: Not applicable *: ACGIH "STEL" Guidelines ND: Not Determined STEL: Short Term Exposure Limits

SECTION 4: FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician Do not induce vomiting

Rinse mouth

SECTION 5: FIRE FIGHTING MEASURES

NFPA Flammability Classification: LEVEL 3 Aerosol

FLASH POINT: Not Determined **FLAMMABLE LIMITS:** UEL 12.8 % LEL 1.0 %

PRODUCT NAME: **McKay Belt Grip**
PRODUCT NUMBER: 50603

SECTION 5: FIRE FIGHTING MEASURES (continued)

EXTINGUISHING MEDIUM: AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Do not use water jet. Keep exposed containers cool with water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse any flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.

Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

SECTION 7: HANDLING AND STORAGE

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Control airborne concentrations below the exposure limits see below. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPEMNT: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. Minimum requirements are: SAFETY GLASSES and GLOVES.

RESPIRATORY PROTECTION (SPECIFY TYPE): If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION: For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier)

BODY PROTECTION: To prevent repeated or prolonged skin contact, use protective clothing impervious to this product. Selection of specific items such as gloves, boots, apron, or full body suit will depend on operation.

PRODUCT NAME: **McKay Belt Grip**
 PRODUCT NUMBER: 50603

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

OCCUPATIONAL EXPOSURE GUIDELINES:

HAZARDOUS COMPONENTS

	OSHA PEL	ACGIH
Heptane	400 ppm	400 ppm
Acetone	750 ppm	750 ppm
Propane	1000 ppm	NE
Butane	800 ppm	800 ppm

Abbreviations

NE: None established N/A: Not applicable *: ACGIH "STEL" Guidelines ND: Not Determined STEL: Short Term Exposure Limits

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid	COLOR: Amber	ODOR: Mild
SPECIFIC GRAVITY: 0.75-0.85 (Water =1)	pH: N/A	VAPOR DENSITY (Air =1): Heavier Than
VAPOR PRESSURE (mmHg or psig @70°F): 50-70 psig		VISCOSITY (cps @ 70°F) N/D
SOLUBILITY IN WATER % BY WT.: Insoluble		MELTING POINT /FREEZING POINT: N/D
VOLATILE ORGANIC COMPOUNDS (VOCs) Content: 64.3 %		BOILING POINT RANGE: N/D

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable, avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition and direct sunlight.

INCOMPATIBILITY: Avoid contact with strong acids, strong bases, strong oxidizers, aldehydes, alkalis, amines, ammonia, reducing agents, chlorine compounds, may form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, and carbon monoxide,

HAZARDOUS POLYMERIZATION: Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Mild eye irritation.

Skin Contact

Causes skin irritation. Harmful if prolonged contact with skin occurs.

Inhalation

Harmful if inhaled.

Ingestion

Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	5,800 mg/kg rat	>7,426 mg/kg guinea pig	32,000 ppm/ 4h/rat
Dimerized rosin	➤ 4,000 mg/kg Mouse ➤ 4,000 mg/kg Guinea Pig	➤ 2,500 mg/kg rabbit	No data
Resin and rosin acids, methyl ester	➤ 2,000 Rat	➤ 2,500 Rabbit	No data
Heptane	No information	No information	No information
Propane	No information	No information	658 mg/l/4h rat
Butane	No information	No information	30957 mg/m3 4h rat

PRODUCT NAME: **McKay Belt Grip**
PRODUCT NUMBER: 50603

SECTION 12: ECOLOGICAL INFORMATION

No ecological studies have been conducted on this product.

Product/ingredient name	Result	Species	Exposure
Acetone	LC50: 5540 mg/l	Rainbow Trout	96 h
	LC50: 8300 mg/l	Blue Gill Sunfish	96 h
	LC50: 12600-12700 mg/l	Daphnia	48 h
	EC50: 3020 mg/l	Chlorella pyrenoidosa	14 d
	EC50: 14500 mg/l	Photobacterium phosphoreum	15 min
Resin and rosin acids, methyl ester	LL50: >1,000 mg/l	Fathead minnow	96 h
	EL 50: 27 mg/l	Water Flea	48 d
	EL50: > 1,000 mg/l	Selenastrum capricornutum	72 h

ECOTOXICITY: If spilled this any water or soil contaminated may be hazardous to human, animal and aquatic life.

ENVIRONMENTAL FATE: The chemicals in this product are potentially toxic to freshwater and salt water ecosystems. They will normally float on water with their lighter components evaporating rapidly. In stagnant or slow-flowing waterways, a hydrocarbon layer can cover a large surface area. As a result this layer might limit or eliminate natural atmospheric oxygen transport into the water. Which with time could lead to a fish kill or an anaerobic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use. It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: TRANSPORT INFORMATION

DOT STATUS: This material is regulated by the U.S. Department of Transportation (DOT).

PROPER SHIPPING NAME: (to ship on the ocean):

UN1950, AEROSOLS, FLAMMABLE (each not exceeding 1L capacity), 2.1, LTD. QTY

HAZARD CLASS: 2.1

PLACARDS: None Required

PACKING GROUPS: None for aerosols

EMERGENCY RESPONSE GUIDE NO: 126

PRODUCT NAME: **McKay Belt Grip**
PRODUCT NUMBER: 50603

SECTION 15: REGULATORY INFORMATION

311/312 HAZARD CATEGORIES:

Fire Hazard: YES Pressure Hazard: YES Reactivity Hazard: NO Immediate Hazard: YES Delayed Hazard: NO

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
None Listed.		

FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
Acetone	67-64-1	5-10	5,000

CALIFORNIA PROPOSITION 65 None listed

MASSACHUSETTS RIGHT TO KNOW: Yes

PENNSYLVANIA RIGHT TO KNOW: Yes

NEW JERSEY RIGHT TO KNOW: Yes

Heptane	64742-49-0	35-40
Acetone	67-64-1	5-10
Propane	74-98-6	10-15
Butane	106-97-8	10-15

CALIFORNIA VOC'S: N/A

NFPA RATING AS AN AEROSOL: Level Three

SECTION 16: OTHER INFORMATION

REVISION INFORMATION

VERSION NUMBER: 1.0003

REVISION DATE: 11/14/2005, 3/26/2009, 6/29/2015

PRINT DATE:

ABBREVIATIONS:

N/A: Not Applicable

N/D: Not Determined

NE: Not Established

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

HMIS: Hazardous Materials Information System

NFPA: National Fire Protection Association

EPA: US Environmental Protection Agency NIOSH: National Institute of Occupational Safety and Health

DISCLAIMER OF LIABILITY:

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.